



### Acrylic waterproofing primer

A penetrating water based sealer that binds the substrate particles together on and below the surface, waterproofing and providing a sound base for maximum adhesion for Acrylic flexible waterproofing membranes. Also serves as a water repellent solution for wet area walls & floors as specified in Waterproofing of wet areas AS3740-2004 regulations.

Suitable for use on cement render, concrete, brick and blocks and applied by brush or airless sprayer. One coat application with coverage ranging from 3 – 6 m<sup>2</sup>/litre, depending on the porosity of the substrate.

Acrylic waterproofing membrane can be applied onto the primed surfaces while the surfaces are still damp.

Surfaces must be sound and clean of grease, oil, dust and other contaminants.

Use in well ventilated areas.

Not classified as hazardous to health according to the criteria of the National Health and Safety Commission, Australia.

#### First Aid

**Eyes** Flush eyes with water for at least 15 minutes

**Skin** May cause irritation, Wash affected areas with soap and water.

**Inhalation** May cause irritation, Move subject to fresh air.

**Ingestion** Seek medical attention. Do not induce vomiting unless directed to do so by medical personnel

#### Handling & Storage

As with all chemical products good industrial hygiene procedures should be followed when using this product.

Wear suitable gloves & goggles and use in well ventilated areas.

Store in well ventilated area and keep container sealed and away from excessive heat and out of direct sunlight.

**KEEP OUT OF REACH OF CHILDREN**