



Single pack reinforced acrylic flexible waterproofing membrane

Two coats are recommended to achieve a dry film thickness of 1.5mm. The final cured product can be elongated up to 200% before tearing and can be over painted with water based acrylic paints.

CURING

7 days at 20°C @ 50% relative humidity. Protect from rain for the first 24 hours.

Cold damp conditions increase curing time & hot dry conditions reduces curing time.

Do not thin material or add filler.

Not for areas where continuous rising damp is a problem or hydrostatic pressure is present.

Shower alcoves should be allowed 72 hours to cure before tiling.

Immersed applications must be allowed to cure for 28 days before being put into use.

SURFACE PREPARATION

Surfaces must be sound and clean of grease, oil, dust and other contaminants.

Prime with Acrylic waterproofing primer prior to application.

Use in well ventilated areas.

First Aid

Eyes Flush eyes with water for at least 15 minutes

Skin May cause irritation, Wash affected areas with soap and water.

Inhalation May cause irritation, Move subject to fresh air.

Ingestion Adverse effects are not expected.

Handling & Storage

As with all chemical products good industrial hygiene procedures should be followed when using this product.

Wear suitable gloves & goggles and use in well ventilated areas.

Store in well ventilated area and keep container sealed and away from excessive heat and out of direct sunlight.

KEEP OUT OF REACH OF CHILDREN