



Grout seal 16

Waterproofing solution designed to penetrate into existing sound grout and waterproof it. Brushed or sprayed on with an airless sprayer it is quickly absorbed by the grout and the excess can be wiped off with a dry cloth leaving no streaks on glazed tiles. The depth of penetration will be affected by the additives in the different grouts used; tests have shown penetration levels of between 5 – 10mm.

Coverage will depend on the porosity and thickness of the grout lines, as a guide 20 – 30m² of tiled surface to the litre

The grout must be sound and free of excessive soap build up, can be cleaned with household detergent in warm water prior to sealing.

Grout seal 16 will not bridge cracks in the grout, if cracks are evident they will have to be filled prior to applying the sealer.

The solution is water based and environmentally friendly, clean all equipment with water.

Use in well ventilated areas.

First Aid

Eyes Flush eyes with water for at least 15 minutes

Skin May cause irritation, Wash affected areas with soap and water.

Inhalation May cause irritation, Move subject to fresh air.

Ingestion Adverse effects are not expected.

Handling & Storage

Grout Seal 16 is classified as a non-hazardous material.

As with all chemical products good industrial hygiene procedures should be followed when using this product.

Wear suitable gloves & goggles and use in well ventilated areas.

Store in well ventilated area and keep container sealed and away from excessive heat and out of direct sunlight.

KEEP OUT OF REACH OF CHILDREN