



## Render Water Repellent

Render Water Repellent is a water based sealer suitable for all cement based renders, it penetrates into the body of the render and once dry it provides a waterproof zone where moisture can not penetrate. By reducing water penetration it stops efflorescence and water-borne staining and significantly increases the life of paints & coatings.

Render Water Repellent is Non-Toxic, will not peel or blister is UV and alkali stable and under normal circumstances will not significantly alter the appearance of the rendered walls. However it is strongly recommended that a test be carried out prior to application.

Surfaces should be clean, dry, firm and free from oil or previously applied sealers or coatings. If required, surfaces can be washed with a strong detergent/degreaser and rinsed with water. Any cracked or damaged areas should be filled with cement based filler and allowed to cure & dry. Apply the product by brush, roller or airless sprayer, making sure that the surface is saturated. If solution is quickly absorbed apply a second coat at a rate that shows the product running down the surface. Any product remaining on the surface after 5 minutes should be wiped off. (So as to not create an uneven surface) REMOVE PRODUCT FROM AREAS YOU DO NOT WISH TO TREAT IMMEDIATELY WITH A DAMP CLOTH OR SPRAY. Do not apply if rain or extreme weather conditions are expected.

Coverage rate will vary from 2-4m<sup>2</sup> per litre/coat and always test a small area to ensure suitability of the product to your requirements. Shake/Stir well prior to use

Water repellence in 24 hours and full cure achieved in 7 days.

- Physical Data – Milky white in appearance
- Solids content of < 50% by weight
  - Specific gravity of 1.0 @ 20 °C
  - pH of 7 – 8
  - Soluble in water
  - No VOC content
  - Non flammable
  -

### First Aid

**Eyes** Flush eyes with water for at least 15 minutes

**Skin** May cause irritation, Wash affected areas with soap and water.

**Inhalation** May cause irritation, Move subject to fresh air, if breathing is difficult, give oxygen.

**Ingestion** can cause gastrointestinal irritation, Give 2 glasses of water to drink to dilute.

Consult a Doctor. **DO NOT INDUCE VOMITTING**

### Handling & Storage

Non-Hazardous according to criteria of Worksafe Australia.

The product is classified as a non-hazardous material. However, as with all chemical products good industrial hygiene procedures should be followed when using this product.

Wear suitable gloves & goggles and use in well ventilated areas.

Store in well ventilated area and keep container sealed and away from excessive heat and out of direct sunlight.

**KEEP OUT OF REACH OF CHILDREN**