



Stain Repellent Sealer

Stain Repellent Sealer is water-based product that provides a durable, penetrating and transparent protective barrier against oil, water and stains on concrete, brick, block and most masonry products. One application will provide oil and water repellency, stain resistance and allows for easy stain cleanup.

Surfaces treated with Stain Repellent Sealer should be cleaned ASAP after contaminations with oil, grease, and red wine etc. Spillages are harder to clean up the longer they are left and increases the chances of permanent staining. Surfaces that have been cleaned may need to be re-treated.

Stain Repellent Sealer chemically bonds to the surface and provides vapour permeable and durable protection on most masonry surfaces. The product is stable and under normal circumstances will not significantly alter the appearance of the masonry products. However it is strongly recommended that a test be carried out prior to application as some masonry products have pigments that may be highlighted after application.

Surfaces should be clean, dry, firm and free from oil or previously applied sealers or coatings. If required, surfaces can be washed with a strong detergent/degreaser and rinsed with water. Any cracked or damaged areas should be filled with cement based filler and allowed to cure & dry. Apply the sealer by brush, roller or airless sprayer, making sure that the surface is saturated. If solution is quickly absorbed apply a second coat at a rate that shows the sealer pooling on the surface. Any product remaining on the surface after 5 minutes should be wiped off. (So as to not create an uneven surface) REMOVE PRODUCT FROM AREAS YOU DO NOT WISH TO TREAT IMMEDIATELY WITH A DAMP CLOTH OR SPRAY. Do not apply if rain or extreme weather conditions are expected.

Coverage rate will vary from 2-10m² per litre/coat and always test a small area to ensure suitability of the product to your requirements. Shake/Stir well prior to use

Stain repellence in 24 hours and full cure achieved in 7 days.

- Physical Data – Milky in appearance
- Solids content of < 20% by weight
 - Specific gravity of 1.0 @ 20 °C
 - pH of 6 – 6.5
 - Soluble in water
 - Low VOC content
 - Non flammable

First Aid

Eyes Flush eyes with water for at least 15 minutes

Skin May cause irritation, Wash affected areas with soap and water.

Avoid inhaling vapours & fine mist. Move subject to fresh air, if breathing is difficult, give oxygen.

Ingestion can cause gastrointestinal irritation, Give 2 glasses of water to drink to dilute.

Consult a Doctor. **DO NOT INDUCE VOMITTING**

Handling & Storage

Hazardous according to criteria of Worksafe Australia.

The product is classified as a hazardous material, as with all chemical products good industrial hygiene procedures should be followed when using this product.

Wear suitable gloves & goggles and use in well ventilated areas.

Store in well ventilated area and keep container sealed and away from excessive heat and out of direct sunlight.

KEEP OUT OF REACH OF CHILDREN